

AGA OVERSEAS PVT. LTD.

www.agaoverseas.com







- info@agaoverseas.com
- +91 8830025846
- aga overseas













ABOUT US



AGA OVERSEAS PVT. LTD. AGA OVERSEAS PVT. LTD.

is an ISO 9001:2015 certi ded company engaged in Importing & Exporting

We provide superior quality products which are widely accepted by our clients at a reasonable price.

WE ARE MANUFACTURER, SUPPLIER, TRADER, IMPORTER & EXPORTER

PRODUCT



Refined Castor oil (F.S.G./B.S.S)-

Refined castor oil is yellow viscous liquid free from suspended matter and is insoluble in water.

The oil obtained from the seeds of this plant is a very useful raw material in many industries like soap, surface coatings, cosmetics, pharmaceuticals, perfumes, greases and lubricants etc. FIRST SPECIAL GRADE CASTOR OIL is produced by refining

Commercial Grade Castor Oil through bleaching and filtering process. Bleaching is done using Bleaching Earth and Activated Carbon, which helps in reducing coloring pigments or impurities and moisture content.

SPECIFICATION



DESCRIPTION	SPECIFIC RANGE
Refractive Index	1.477 — 1.481
Moisture & Volatile Matter	0.25 Percent Max
Insoluble Impurities	0.02 percent Max
Free Fatty Acid	1 Percent Max
Acid Value	2.00 Max
Iodine Value	TM .
	8. 90 Percent
(By Wiss, gl 2 / 100g)	
Acetyl Value	AGA 1 Min
Saponification Value	OVERSEAS
(mgKoH/gm)	7 – 187
(
Unsaponification Matter	1.00% Max
Hydroxyl Value	160 - 168
Relative Density 15/15.5 DC	0.958 - 0.969
Viscosity Gardner- Holdt	U-V
Color on Lovibond	20 Yellow, 2.0 Red Max
Appearance 25 DC	Clear and free from suspended matter
Odor	Slight, Characteristic
Ricinoleic Acid Content	85 Percent Min

www.agaoverseas.com

APPLICATIONS



- · It is used for various industrial applications and generally in manufacturing of textile chemicals or as wetting agents for inks, coatings and adhesives.
- It is used as an ingredient in pharmaceutical and cosmetic applications
- It is used as lubricant component of coatings for vitamin and mineral Tablets.
- It is used as a dielectric material for electrical condensers
- .It is used to manufacture polyurethane casting resins
- .It is used in hydraulic $\square\,\text{uids}$ for
- automobiles, trucks and machinery
- .It is used as an ingredient for petroleum
- oil-□eld de-emulsi□cation

PACKAGING



- Standard Packing
 Unit 20 FT Container
- 2) Packing Flexi Bag22MT per 20FT Full Container Load,
- 3) Packing ISO Tank22MT per 20FT ISO Full Container Load,
- 4) Packing Steel Drum 16MT per 20FT FCL (200Kg Drum),
- 5) Packing HDPE Drum 16MT per 20FT FCL (200Kg Drum),
- 6) Packing IBC Tank 1000 Kgs.IBC X 20 = 20MT per 20FT FCL

CONTACT US



Address:

AGA OVERSEAS PVT. LTD. Office No.8, Mezzainne Floor Jagadish sankul Near KBT Circle, Thatte Nagar, Gangapur Road, Nashik, Mahashtra 422005, India.

- info@agaoverseas.com
- +91 8830025846
- aga overseas

Follows Us on () (in)









www.agaoverseas.com